

Typen
Übersicht

Chassis

Batterieladegeräte

Kapitel 1. Reihe C

Typenübersicht Chassis

Gerätenummer	Spg.	Strom	Typenbezeichnung	Abmessungen (LxBxH) mm	Gewicht	Kapitel Katalog
KC 10601	6 V	1 A	C106-1	160x100x67	1,0 kg	1.1.1.
KC 11201	12 V	1 A	C112-1	160x100x67	1,0 kg	1.1.1.
KC 11202	12 V	1,5 A	C112-1,5	160x100x75	1,2 kg	1.1.2.
KC 331205	12 V	5 A	C11-312-5	121,8x90x56	0,6 kg	1.2.8.
KC 331206	12 V	6 A	C11-312-6	121,8x90x56	0,6 kg	1.2.8.
KC 31206	12 V	6 A	C2-312-6	191x120x60	0,6 kg	1.2.2.
KC 31212	12 V	12 A	C3-312-12	250x 224x92	3,4 kg	1.2.3.
KC 31220	12 V	20 A	C3-312-20	250x 234x92	3,8 kg	1.2.3.
KC 41235	12 V	35 A	C412-35	230x130x120	4,0 kg	1.3.
KC 31250	12 V	50 A	C5-312-50	338x260x110	7,0 kg	1.2.6.
KC 12401	24 V	1 A	C124-1	160x100x67	1,1 kg	1.1.1.
KC 12402	24 V	1,5 A	C124-1,5	160x100x75	1,2 kg	1.1.2.
KC 332403	24 V	3 A	C11-324-3	121,8x90x56	0,6 kg	1.2.8.
KC 32404	24 V	3 A	C2-324-3	191x120x60	0,6 kg	1.2.2.
KC 32406	24 V	6 A	C2-324-6	191x120x60	0,7 kg	1.2.2.
KC 32410	24 V	10 A	C3-324-10	250x 234x92	3,4 kg	1.2.3.
KC 32412	24 V	12 A	C3-324-12	250x 234x92	4,0 kg	1.2.3.
KC 42412	24 V	12 A	C424-12	230x130x120	3,5 kg	1.3.
KC 32416	24 V	16 A	C3-324-16	354x205x100	4,2 kg	1.2.4.
KC 32420	24 V	20 A	C3-324-20	275x215x92	5,5 kg	1.2.5.
KC 42425	24 V	25 A	C424-25	230x130x120	4,0 kg	1.3.
KC 32430	24 V	30 A	C5-324-30	338x260x110	7,5 kg	1.2.6.
KC 32450	24 V	50 A	C5-324-50	338x260x110	8,0 kg	1.2.6.
KC 324100	24 V	100 A	C6-324-100	470x340x120	16,0 kg	1.2.7.
KC 33604	36 V	4 A	C2-336-4	191x120x60	0,7 kg	1.2.2.
KC 33614	36 V	14 A	C3-336-14	250x 234x92	4,0 kg	1.2.3.
KC 33635	36 V	35 A	C5-336-35	275x 215x92	5,5 kg	1.2.5.
KC 34803	48 V	3 A	C2-348-3	191x120x60	0,7 kg	1.2.2.
KC 34806	48 V	6 A	C3-348-6	250x 234x92	4,0 kg	1.2.3.
KC 44806	48 V	6 A	C448-6	230x130x120	3,5 kg	1.3.
KC 34810	48 V	10 A	C3-348-10	275x 215x92	5,5 kg	1.2.5.
KC 44812	48 V	12,5 A	C448-12,5	230x130x120	4,0 kg	1.3.
KC 34825	48 V	25 A	C5-348-25	338x260x110	8,0 kg	1.2.6.
KC 34850	48 V	50 A	C6-348-50	470x340x120	16,0 kg	1.2.7.
KC 36002	60 V	2,5 A	C2-360-2,5	191x120x60	0,7 kg	1.2.2.
KC 46005	60 V	5 A	C460-5	230x130x120	3,5 kg	1.3.
KC 36008	60 V	8 A	C3-360-8	275x 215x92	5,5 kg	1.2.5.
KC 46010	60 V	10 A	C460-10	230x130x120	4,0 kg	1.3.
KC 36020	60 V	20 A	C5-360-20	338x260x110	8,0 kg	1.2.6.
KC 36040	60 V	40 A	C6-360-40	470x340x120	16,0 kg	1.2.7.
KC 47208	72 V	8 A	C472-8	230x130x120	4,0 kg	1.2.2.